

Safety Data Sheet (SDS) Liquefied Petroleum Gas (LPG)



| 1. Product And Company Details | | |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| Product name | Liquefied Petroleum Gas (LPG) (unodourised and odourised) | |
| Other names | LPG, LP Gas, Propane, Rockgas | |
| Use | Automotive, residential and commercial fuel | |
| Company | Rockgas Limited, c/o Gas Service NZ, 42 Connett Rd West, Bell Block, New Plymouth 4312 | |
| Telephone | 0800 762 542 | |
| Emergency telephone | Fire Service: 111 Rockgas: 0800 427 345 | |
| 2. Hazards Identification | | |
| UN Number | Liquefied Petroleum Gas (LPG): | 1075 |
| | Propane: | 1978 |
| | Butane: | 1011 |
| Hazchem Code | 2YE | |
| Dangerous Goods (HSNO) Class | 2.1.1A | |
| GHS Classification | Category: Flammable Gas Category 1A | |
| | Signal Word: Danger | |
| | Hazard Statement: Extremely flammable gas | |
| Health Hazards | LPG acts as an asphyxiant if present in high concentrations. Overexposure to LPG can cause light-headedness and drowsiness. Greater exposure may also cause unconsciousness. Contact with liquid may also cause cold burns. | |
| Environmental Hazards | Not classified as an Environmental Hazard | |
| Precautionary Statements | Keep away from heat, hot surfaces, sparks, open flames and other ignitions sources. No smoking. Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so. | |
| 3. Composition/Information on Ingredients | | |
| Chemical Entity | CAS Number | Proportion |
| LPG | 68476-85-7 | 100% maximum |
| Propane | 74-98-6 | 100% maximum |
| Butane | 106-97-8 | 50% maximum |
| Ethyl Mercaptan | 75-08-1 | 0.0017% minimum (odourised LPG) |
| 4. First Aid Measures | | |
| Swallowed | Due to high volatility of product, this is not likely to occur. | |
| Eyes | <ul style="list-style-type: none"> ▪ Do not delay – flood eyes gently with clean tepid water (not hot) for at least 15 minutes, or flush eyes for as long as possible with sterile saline solution. ▪ Seek medical attention. | |
| Skin | <ul style="list-style-type: none"> ▪ Immediately bathe the area with large quantities of water (preferably tepid) for at least 15 minutes. ▪ If possible, remove any clothing splashed with liquid LPG that is not sticking to the skin. | |

Safety Data Sheet (SDS) Liquefied Petroleum Gas (LPG)



| | |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | <ul style="list-style-type: none"> ▪ Place the injured person in a warm area and gradually rewarm the affected areas to normal body temperature. ▪ Do not apply any form of direct heat. ▪ Keep the person warm and comfortable. ▪ Loosen restrictive clothing. ▪ Gently cover the affected area with glad wrap or a wet, (not fibrous) material, ensuring that circulation is not restricted. ▪ Do not give anything to eat or drink. ▪ Never leave the injured person unattended. ▪ Keep contaminated clothing away from ignition sources as some gas may be given off during thawing. ▪ Seek medical attention. |
| Inhaled | <ul style="list-style-type: none"> ▪ Remove victim to fresh air. ▪ If breathing has stopped, or irregular, apply artificial respiration. ▪ Seek medical attention. |
| Advice to doctor | Treat symptomatically. |

5. Fire Fighting Measures

| | |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fire/Explosion hazard | <ul style="list-style-type: none"> ▪ Evacuate area if required and remove ignition sources. ▪ Cut off gas supply if safe to do so – do not endanger life. ▪ Do not extinguish an LPG fire – allow gas to burn out. ▪ Drench and cool the LPG tank or cylinder with water spray from a safe distance. ▪ Wait for Emergency Services at a safe distance. <p>Note: If ignition has occurred and water is not available or can't be sprayed on the tank or cylinder safely, the metal may weaken from the heat and explode. The potential affected area should be evacuated immediately, and emergency services notified from a safe location.</p> <p>Note: If it is essential to extinguish the fire then use only dry chemical powder extinguishers.</p> |
| Combustion products | <ul style="list-style-type: none"> ▪ Carbon dioxide, water vapour, traces of carbon monoxide and nitrogen oxides. ▪ Fumes, smoke, carbon monoxide and aldehydes can be formed during incomplete combustion. <p>Note: Fire fighters may need self-contained breathing apparatus.</p> |
| Advice to Firefighters | <ul style="list-style-type: none"> ▪ Temperatures in a fire may cause the tank or cylinder(s) pressure relief devices to open and release gas, or eventually rupture. ▪ Cool the tank or cylinder(s) exposed to fire by applying water spray from a protected location. |

6. Accidental Release Measures

| | |
|----------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal precautions, protective equipment and emergency procedures | <ul style="list-style-type: none"> ▪ Evacuate area if required and remove ignition sources. ▪ Stop flow of gas/liquid if safe to do so – do not endanger life. ▪ Move people from potential affected area, keep up-wind. ▪ Notify emergency services. ▪ Stop flow of gas/liquid if safe to do so. ▪ Spray water mist to disperse the gas cloud but avoid spraying water directly on leaking container as this may increase leakage. ▪ Prevent spillage from spreading or entering underground drains by blocking with wetted cloths, sand or earth. ▪ LPG is heavier than air and may pool in low areas |
|----------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Safety Data Sheet (SDS) Liquefied Petroleum Gas (LPG)



7. Handling and Storage

| | |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Safe handling | <ul style="list-style-type: none">▪ Use of safe work practices are recommended to avoid eye or skin contact.▪ Do not roll cylinders horizontally and avoid dragging cylinders across uneven or rough surfaces.▪ The uncontrolled release of a gas under pressure may cause physical harm. |
| Conditions for safe storage | <ul style="list-style-type: none">▪ Do not store near sources of ignition or incompatible materials.▪ Cylinders should be stored upright, on a firm and stable surface.▪ Cylinders should be stored in an accessible, well-ventilated area. |
| Additional details | <ul style="list-style-type: none">▪ Health and Safety at Work (Hazardous Substances) Regulations 2017▪ Hazardous Substances and New Organisms Act (HSNO) 1996▪ NZS 5433 Transport of Dangerous Goods on Land 2020▪ Relevant GasNZ Codes of Practice▪ AS/NZS 1596 Storage and Handling of LP Gas 2014 |

8. Exposure Controls and Personal Protection

Workplace exposure standards and biological exposure indices Edition 15 (WorkSafe February 2025):

- Propane is a simple asphyxiant and displaces oxygen from air. It presents an explosion hazard.
 - Butane TWA 800 ppm, 1900 mg/m³
 - LPG TWA 1,000 ppm, 1800 mg/m³

| | |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ignition sources | <ul style="list-style-type: none">▪ Provide suitable ventilation to minimise an explosive atmosphere environment.▪ Do not bring sources of ignition into a potentially hazardous area atmosphere.▪ Use only intrinsically safe electrical equipment. Do not bring items such as mobile phones, radios, cameras and other non-intrinsically safe electrical equipment into a potentially hazardous area atmosphere▪ Only use appropriate intrinsically safe (certified) tools and equipment in a potentially hazardous area atmosphere <p>Note: Hazardous area atmosphere zones are not always easy to define or measure, these zone extents may need to be clarified by a competent person.</p> |
| Ventilation | Maintain adequate ventilation. Note: LPG appliances can be hazardous when used in a poorly ventilated room. |
| Usage | <ul style="list-style-type: none">▪ Cylinders other than in-use forklift or automotive cylinders, must be used in the upright position.▪ Use only equipment approved for LPG installations and installed in accordance with HSNO, Health and Safety at Work (Hazardous Substances) Regulations 2017, relevant GasNZ Codes of Practice and, if applicable, AS/NZS 1596:2014 and/or the Gas Act 1992 (as amended). |

Safety Data Sheet (SDS) Liquefied Petroleum Gas (LPG)



To protect against accidental release of pressurised LPG when there is a possibility of LPG liquid release (e.g. transferring):

Eyes/face

Wear full wrap-around safety glasses or goggles.



Hands

Wear appropriate thermal insulating gloves.

Body

Wear reduced static full body cover, cotton or other material with equivalent static and flame-resistant properties.

Respiratory

Where an inhalation risk exists, wear self-contained breathing apparatus.

9. Physical and Chemical Properties

| | | | | |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|----------------|---------------|--------------------------|
| Appearance | Colourless gas, liquid under pressure. Typically has an unpleasant odour due to the addition of ethyl mercaptan when odourised. | | | |
| | | Propane | Butane | LPG Mix (typical) |
| Boiling Point (at atmospheric pressure) | | -42°C | 0°C | n/a |
| Vapour Pressure | -10°C | 256 kPa | -4 kPa | 185 kPa |
| | 0°C | 388 kPa | 40 kPa | 292 kPa |
| | 10°C | 552 kPa | 95 kPa | 424kPa |
| | 20°C | 757kPa | 172 kPa | 593 kPa |
| | 30°C | 1004 kPa | 266 kPa | 796 kPa |
| Solubility in Water | | 75 mg/l | 88 mg/l | |
| Specific Gravity Liquid (Water = 1) | | 0.508 | 0.573 | 0.537 |
| Specific Gravity Gas (Air = 1) | | 1.58 | 2.06 | 1.73 |
| Flash Point | | -105°C | -60°C | -81°C |
| Flammability Limits | | 2.2 – 9.5% | 1.5 – 9.0% | 2 – 10% |
| Auto Ignition Temperature | | 468°C | 430°C | 450°C |

10. Stability and Reactivity

- Stable under normal ambient conditions of storage and use.
- Avoid heat sources, sparks, open flames, and other ignition sources.

Can react violently with oxidising agents – chlorine, pool chlorine or acids (e.g. nitric acid), heat and ignition sources.

11. Toxicological Information

Health effects from acute exposure

| | |
|------------------|-------------------------------------------------------------------------------------------------------|
| Swallowed | Due to high volatility of product, this is not likely to occur. |
| Eyes | Vaporising liquid will cause severe damage. Vapour will cause irritation. |
| Skin | Vaporising liquid or liquid contact can result in cold burns. |
| Inhaled | <ul style="list-style-type: none">May cause light-headedness, dizziness and drowsiness. |

Safety Data Sheet (SDS) Liquefied Petroleum Gas (LPG)



| | |
|-----------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | <ul style="list-style-type: none">Excessive exposure may cause unconsciousness or even death, due to asphyxiation (refers to vapour not liquid). |
| No chronic systemic effects reported from industrial exposures. | |
| Carcinogenicity | No known effect. |
| Mutagenicity | No known effect. |
| Teratogenicity | No known effect. |

12. Ecological Information

| | |
|----------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Ecotoxicity (aquatic and terrestrial) | LPG will vaporise rapidly when released to atmosphere. There are no known adverse ecological effects. |
| Persistence and degradability | LPG will vaporise rapidly when released to atmosphere. There are no known adverse ecological effects. |
| Potential to bioaccumulate | LPG will vaporise rapidly when released to atmosphere. There are no known adverse ecological effects. |
| Mobility in soil | LPG will vaporise rapidly when released to atmosphere. There are no known adverse ecological effects. |
| Other adverse effects | LPG will vaporise rapidly when released to atmosphere. There are no known adverse ecological effects. |

13. Disposal Considerations

Contact Rockgas if disposal of LPG is required.

- LPG cylinders should be returned to the owning organisation stamped on the cylinder when no longer required.
- Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not attempt to clean since residue is difficult to remove.
- Do **NOT** pressurise, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks and other sources of ignition. They may explode and cause injury or death.
- Disposal of material must be carried out in accordance with Hazardous Substances (Disposal) Notice 2017 and the HSNO Act.

14. Transport Information

| | | | |
|---------------------------|-----------------------------------------------------------------|----------------|--------------------------------------|
| Transport | Transport of LPG is controlled in accordance with NZS 5433:2020 | | |
| Shipping name | Propane | Butane | Liquefied Petroleum Gas (LPG) |
| UN Number | 1978 | 1011 | 1075 |
| UN DG Class | 2.1 | 2.1 | 2.1 |
| Subsidiary Risk(s) | None allocated | None allocated | None allocated |
| Hazchem code | 2YE | 2YE | 2YE |
| Marine Pollutant | No | | |



Safety Data Sheet (SDS) Liquefied Petroleum Gas (LPG)



15. Regulatory Information

| | Propane | Butane | LPG |
|-------------------------|-----------------------------|-----------|-----------|
| EPA Approval Numbers | HSR001010 | HSR000989 | HSR001009 |
| HSNO Group Standard | LPG Liquefied Petroleum Gas | | |
| Poisons schedule number | None allocated | | |

LPG is a prescribed Hazardous Substance and its storage and handling is covered by various pieces of legislation.

16. Other Information

| | |
|------------------|------------------------------------------------------------|
| Acronyms | CAS – Chemical Abstract Service |
| | EPA – Environmental Protection Authority |
| | GHS – Globally Harmonized System |
| | HSNO – Hazardous Substances and New Organisms |
| | TWA – Time-weighted average |
| Standards | AS/NZ 1596 – The Storage and Handling of LPG |
| | NZ 5433 – Transport of Dangerous Goods on Land |
| | NZS 5435 – Specification for Liquefied Petroleum Gas (LPG) |